



BARITAINER® 20L, 13L JERRICANS

**COST
EFFECTIVE**

**REPLACES LINED
STEEL CANS**

**REPLACES
FLUORINATED**

UN Y RATED

**UL 94 HB
CERTIFIED**

IMPACT RESISTANT

**NO PFAS, PFOS
EXPOSURE**

RECYCLABLE

DIMENSIONS:

| Volume | 13L/3.5G/Overflow=3.6G | 20L/5.3G/Overflow=21.2L | 5G / Overflow=5.2G |
|----------------|------------------------|-------------------------|------------------------|
| Weight | 840-880g | 1200-1250g | 1150-1200g |
| Length | 11.16" | 11.16" | 11.16" |
| Width | 10.18" | 10.18" | 10.18" |
| Height | 10.42" | 15.11" | 14.21" |
| Closure | 70mm 6tpi Ratchet Neck | 70mm 6tpi Ratchet Neck | 70mm 6tpi Ratchet Neck |
| Wall Thickness | .030-.033 inches | .037-.038 inches | .037-.038 inches |

KEY ATTRIBUTES:

KORTRAX® Barrier Resin (BR) HDPE Mono-Layer Mixture Jerricans can be used to safely transport solvent-based products such as household chemicals, industrial chemicals, cleaning solvents, adhesives, wood preservatives, automotive additives, and agricultural chemicals. They may also be used to safely transport foodstuffs such as flavors, fragrances and essential oils.

SHIPPING DATA

- Pallet Count: 96 units/20L; 112 units/5G; 144 units/13L.
- 30 pallets per truckload.
- Freight Class: 250.
- GW w Pallet: 275 - 300lbs.
- All Baritainers® shipped with dust cover, tray stacked and shrink wrapped.

ADDED FEATURES & BENEFITS:

- Engineered bottom seam for increased seal integrity.
- Closed Vent with 22mm Cap for plug splash back mitigation.
- Standard colors are blue, white & natural.
- All composition materials are FDA and EU Compliant.

MATERIAL SPECIFICATIONS:

Description: KORTRAX®/HDPE Mono-Layer Mixture with environmental stress crack and aggressive chemical resistance.

Screw Cap/Neck:

70mm tamper evident closure with ¾" NPT center reducer and EPDM gasket

Pullout Spouts: Available.



(949) 633-1115

info@BarrierPlastics.com
3972 Barranca Parkway Ste. #1468
Irvine, CA 92606

www.BarrierPlastics.com