



BARITAINER® 12L, 15L, 20L JERRICANS

**COST
EFFECTIVE**

**REPLACES LINED
STEEL CANS**

**REPLACES
FLUORINATED**

UN Y RATED

CAPTIVE BACK VENT

IMPACT RESISTANT

**NO PFAS, PFOS
EXPOSURE**

RECYCLABLE

DIMENSIONS:

Volume	12L/3G/Overflow=3.2G	20L/5.3G/Overflow=5.6G	15L/ 4G/Overflow=4.3G
UN Rating	Y 1.8 100kpa	Y 1.8 100kpa	Y 1.8 100kpa
Length	11 25/32"	11 25/32"	11 25/32"
Width	9 3/4"	9 3/4"	9 3/4"
Height	9 7/8"	15 11/16"	12 3/8"
Closure	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E
Wall Thickness	.037-.038 inches	.037-.038 inches	.037-.038 inches

KEY ATTRIBUTES:

KORTRAX® Barrier Resin (BR) HDPE Mono-Layer Mixture Jerricans can be used to safely transport solvent-based products such as household chemicals, industrial chemicals, cleaning solvents, adhesives, wood preservatives, automotive additives, and agricultural chemicals. They may also be used to safely transport foodstuffs such as flavors, fragrances and essential oils.

SHIPPING DATA

- Pallet Count: 96 units/20L; 96 units/15L; 128 units/12L.
- 30 pallets per truckload.
- Freight Class: 250.
- GW w Pallet: 230-270lbs.
- All Baritainers® shipped with dust cover, tray stacked and shrink wrapped.

ADDED FEATURES & BENEFITS:

- Engineered bottom seam for increased seal integrity.
- Standard colors are blue, black, white & natural.
- All composition materials are FDA and EU Compliant.
- 21mm T/E Captive Back Vent.

MATERIAL SPECIFICATIONS:

Description: KORTRAX®/HDPE Mono-Layer Mixture with environmental stress crack and aggressive chemical resistance.

Screw Cap/Neck: Either DIN60 T/E Cap w Alveolit gasket; or, 70mm 6tpi T/E Cap w 3/4" NPT center reducer & EPDM gasket.



(949) 633-1115

info@BarrierPlastics.com
3972 Barranca Parkway Ste. #1468
Irvine, CA 92606

www.BarrierPlastics.com