



# BARITAINER® 12L, 15L, 20L JERRICANS

**COST  
EFFECTIVE**

**REPLACES LINED  
STEEL CANS**

**REPLACES LETHAL  
FLUORINATED**

**UN Y RATED**

**CHEMICAL RESISTANT**

**UL 94B CERTIFIED**

**NO PFAS, PFOS  
EXPOSURE**

**RECYCLABLE**

## DIMENSIONS:

Volume	12L/3G/Overflow=3.2G	20L/5.3G/Overflow=5.6G	15L/ 4G/Overflow=4.3G
UN Rating	Y 1.8 100kpa	Y 1.8 100kpa	Y 1.8 100kpa
Length	11 25/32"	11 25/32"	11 25/32"
Width	9 3/4"	9 3/4"	9 3/4"
Height	9 7/8"	15 11/16"	12 3/8"
Closure	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E
Wall Thickness	.037-.038 inches	.037-.038 inches	.037-.038 inches

KORTRAX® Barrier Resin (BR) HDPE Mono-Layer Mixture Jerricans can be used to safely transport solvent-based products such as household chemicals, industrial chemicals, cleaning solvents, adhesives, wood preservatives, automotive additives, and agricultural chemicals. They may also be used to safely transport aromatic foodstuffs such as flavors, fragrances and essential oils.

## SHIPPING DATA

- Pallet Count: 96 units/20L; 96 units/15L; 128 units/12L.
- 30 pallets per truckload.
- Freight Class: 250.
- Baritainer Tare Wt.: 1100-1300g
- GW w Pallet: 230-270lbs.
- All Baritainers® shipped with dust cover, tray stacked and shrink wrapped.

## ADDED FEATURES & BENEFITS:

- Standard colors are blue, black, white & natural.
- All composition materials are **FDA and EU Compliant**.
- 21mm T/E Captive Back Vent available.

## MATERIAL SPECIFICATIONS:

**Description:** KORTRAX®/HDPE mono-layer mixture with environmental stress crack and aggressive chemical resistance.

**Kortrax BR50:** Standard amount of Kortrax is nominally 7% of inner layer. Amount may be adjusted depending on the application.

**Screw Cap/Neck:** Either DIN60 T/E Cap w Alveolit gasket; or, 70mm 6tpi T/E Cap w 3/4" NPT center reducer & EPDM gasket. Vented Caps available.



**(949) 633-1115**

**info@BarrierPlastics.com**  
3972 Barranca Parkway Ste. #1468  
Irvine, CA 92606

[www.BarrierPlastics.com](http://www.BarrierPlastics.com)