

BARITAINER® JERRICANS



DIMENSIONS:

Volume	4L	5L	10L
Weight	340-360g	370-390g	550-650g
Length	7.82"	7.82"	9.25"
Width	6.50"	6.50"	7 5/8"
Height	6.75"	8.25"	12 1/16"
UN Rating	UN Y 1.4	UN Y 1.4	UN Y 1.8
Neck	DIN55	DIN55	DIN60

KEY ATTRIBUTES:

KORTRAX® BARITAINER jerricans can be used to safely transport solvent-based products such as household chemicals, industrial chemicals, cleaning solvents, adhesives, wood preservatives, automotive additives, and agricultural chemicals. They may also be used to safely transport foodstuffs such as flavors, fragrances and essential oils.

COMPOSITION:

Body: KORTRAX® BR50 and Chemically Resistant HDPE Mixture.

Screw Cap: HDPE, Alveolit Liner.

FDA, EU Statement: all components are FDA, EU Compliant.

MATERIAL

SPECIFICATIONS:

Description: UN rated KORTRAX BR50/HDPE mono-layer mixture extrusion blow-molded tight heads.

Kortrax BR50: Standard amount of Kortrax in the 4L, 5L is nominally 5%; the 10L is nominally 7%. Amount may be adjusted depending on the application.

Screw Cap/Neck: DIN55 or DIN60 T/E closure with Alveolit gaskets. Sockets for tightening caps available. CRC version available.

Colors: White, Natural; custom colors available.

SHIPPING DATA

- 4L: 396 Units Per Pallet
- 5L: 360 Units Per Pallet
- 10L: 200 Units Per Pallet
- Freight Class: 250
- Truckload is 30 Pallets
- All Baritainers® shipped with dust covers, tray stacked and shrink wrapped on 48x40x96 pallets.

INNOVATIVE BARRIER
UN 4L, 5L and 10L
JERRICAN CONTAINERS
RESISTS PERMEATION
AND EVAPORATION
PREVENTING COSTLY
PRODUCT LOSS.

BARITAINER TIGHT HEADS
ARE MANUFACTURED
WITH A KORTRAX BARRIER
RESIN (BR) AND HIGH
DENSITY POLYETHYLENE
(HDPE) RESIN MONO-
LAYER MIXTURE.

REPLACES
FLUORINATION

REPLACES
LINED STEEL CANS

UN Y RATED

RECYCLABLE

NO PFAS, PFOS EXPOSURE

FDA, EU COMPLIANT



(949) 633-1115

info@BarrierPlastics.com
3972 Barranca Parkway Ste. #1468
Irvine, CA 92606

WWW.BARRIERPLASTICS.COM