



BARITAINER® 12L, 15L, 20L JERRICANS

**COST
EFFECTIVE**

**REPLACES LINED
STEEL CANS**

**REPLACES LETHAL
FLUORINATED**

UN Y RATED

CHEMICAL RESISTANT

UL 94B CERTIFIED

**NO PFAS, PFOS
EXPOSURE**

RECYCLABLE

DIMENSIONS:

Volume	12L/3G/Overflow=3.2G	20L/5.3G/Overflow=5.6G	15L/ 4G/Overflow=4.3G
UN Rating	Y 1.8 100kpa	Y 1.8 100kpa	Y 1.8 100kpa
Length	11 25/32"	11 25/32"	11 25/32"
Width	9 3/4"	9 3/4"	9 3/4"
Height	9 7/8"	15 11/16"	12 3/8"
Closure	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E	DIN60 T/E or 70mm T/E
Wall Thickness	.037-.038 inches	.037-.038 inches	.037-.038 inches

KORTRAX® (Pat. Pend.) BR + HDPE Mono-Layer Mixture Jerricans can be used to safely transport solvent-based products such as household chemicals, industrial chemicals, cleaning solvents, adhesives, wood preservatives, automotive additives, and agricultural chemicals. They may also be used to safely transport aromatic foodstuffs such as flavors, fragrances and essential oils.

SHIPPING DATA

- Pallet Count: 96 units/20L; 96 units/15L; 100 units/12L.
- 30 pallets per truckload.
- Freight Class: 250.
- Baritainer Tare Wt.: 1100-1300g
- GW w Pallet: 230-270lbs.
- All Baritainers® shipped with dust cover, tray stacked and shrink wrapped.

ADDED FEATURES & BENEFITS:

- Standard colors are blue, black, white & natural.
- All composition materials are **FDA and EU Compliant**.
- 21/22mm T/E Captive Back Vent available.

MATERIAL SPECIFICATIONS:

Description: KORTRAX® (P.P.)/HDPE mono-layer mixture with environmental stress crack and aggressive chemical resistance.

Kortrax BR50E: Standard amount of Kortrax (P.P.) is nominally 7% of inner layer. Amount may be adjusted depending on the application.

Screw Cap/Neck: Either DIN60 T/E Cap w Alveolit gasket; or, 70mm 6tpi T/E Cap w 3/4" NPT center reducer & EPDM gasket; or, 63mm Crimp. Vented Caps available.



(949) 633-1115
info@BarrierPlastics.com
 301 McCullough Dr., Ste.
 400 Charlotte, NC 28262

www.BarrierPlastics.com